

Interdens® is a BASF Wolman GmbH trademark.

## Interdens® Type 5 / Type 15

Material of building material classification B2 (normal flammability) according to DIN 4102-1


General building approval Z-19.11-483

### Product Description

Interdens® type 5 / type 15 are intumescent, firm plate materials that foam up pressure-free in three dimensions. Special features: Interdens® type 5 / type 15 have minimal material thickness.

### Application Areas

- Indoor applications
- Fire protection doors
- Wooden doors
- Fire protection glazing



### Technical Data

Composition:	Halogen free, foaming construction material on the basis of phosphate
Material structure:	Semi-stiff panel material
Raw density [kg/m³]:	Type 5: 700 to 915 (at 0,6 mm) Type 15: 800 to 1120 (at 1,0 mm)
Start of reaction [°C]:	From ca. 150
Foaming rate [x-times]:	35 to 70 times (350 °C; 20 min; without load)
Direction of action:	Three-dimensional
Forming inflatable body:	Voluminous, thermally insulating layer

### Supplied Forms

Standard dimension:	2000 mm x 1000 mm
Thickness Type 5:	0,6 mm - 0,1 mm / + 0,2 mm
Thickness Type 15:	1,0 mm - 0,1 mm / + 0,2 mm

*Special formats are available on request. The product is manufactured on the basis of the general tolerance DIN ISO 2768-1.*

*Please observe our information for processing and the safety data sheet!*

*If you want to use this product outdoors please contact our application technology service.*

### Note

The information in this brochure is based on our knowledge and experience to date. This information does not release the user from carrying out independent tests and trials due to the various influences when processing and applying our product. It is not possible to derive a guarantee of certain properties or suitability of the product in a concrete application case based on our information. All the descriptions, drawings, photographs, data, conditions, weights etc. included may change without previous announcement; they do not constitute the contractually agreed property of the product. The recipient of our product is responsible to observe any trade mark rights and existing laws and regulations. Adhesive bonds are to be applied according to DIN 2304.