

ROKU® Glue DS

Product Description

ROKU® glue DS is based on a watery sodium silicate solution; it is suitable for gluing absorbent materials. After hardening, the glue achieves extremely high thermal resistances up to + 800 °C.

Application Areas

- Gluing of mineral fibre, plaster, fibre silicate slabs or mineral and rock wool

Technical Data

Composition:	Glue on water glass basis
Material structure:	High-viscous (thick) glue
Raw density [kg/m ³]:	1860
pH-value:	13



Supplied Forms

Container sizes upon request

Please observe our information for processing and the safety data sheet!

Processing and Storage

Processing:	Stir to glue to form a homogenous mass before processing. Use a spatula or suitable devices to apply.
Storage:	Store in a dry place between + 8 °C and + 25 °C; original, closed containers can be stored ca. 9 months after date of filling.

*Ensure that surfaces are free from dust, fat or oil! Close opened containers air-tight and use as fast as possible!
Protect from frost or heat!*

Note

The information in this brochure is based on our knowledge and experience to date. This information does not release the user from carrying out independent tests and trials due to the various influences when processing and applying our product. It is not possible to derive a guarantee of certain properties or suitability of the product in a concrete application case based on our information. All the descriptions, drawings, photographs, data, conditions, weights etc. included may change without previous announcement; they do not constitute the contractually agreed property of the product. The recipient of our product is responsible to observe any trade mark rights and existing laws and regulations. Adhesive bonds are to be applied according to DIN 2304.