

ROKU® MFC 100

Classification E (normal flammability) according to DIN EN 13501-1



Product Description

ROKU® MFC 100 is an ablation fire protection coating on watery basis. The coating ROKU® MFC 100 is free from halogen, solvent and asbestos; it is available as airless (low-viscous) or thick (high-viscous).

Application Areas

- ROKU® System MFS combination sealing
- Horizontal applications
- Pipe and cable ducts
- Construction openings

Technical Data

Composition:	One-component fire protection coating
Material structure:	ROKU® MFC 100 airless: Low-viscous (thin) coating ROKU® MFC 100 TV: High-viscous (thick) coating
Raw density [kg/m ³]:	Ca. 1250
Minimum processing temperature:	Ab 5 °C
pH-value:	7 to 8
Colour:	White

Supplied Forms

ROKU® MFC 100 Airless:	6 kg bucket 12,5 kg bucket
ROKU® MFC 100 TV:	300 ml cartridge 12,5 kg bucket

Please observe our information for processing and the safety data sheet!

Processing and Storage

Processing:	Use suitable devices (spray, spread or roll-on) to apply.
Lagerung:	Store in a dry place between + 2 °C and + 49 °C; original, closed containers/cartridges can be stored ca. 2 years after date of filling.

Ensure that surfaces are free from dust, fat or oil! Close opened cartridges/containers air-tight and use as fast as possible!

Note

The information in this brochure is based on our knowledge and experience to date. This information does not release the user from carrying out independent tests and trials due to the various influences when processing and applying our product. It is not possible to derive a guarantee of certain properties or suitability of the product in a concrete application case based on our information. All the descriptions, drawings, photographs, data, conditions, weights etc. included may change without previous announcement; they do not constitute the contractually agreed property of the product. The recipient of our product is responsible to observe any trade mark rights and existing laws and regulations.