

ROKU® Strip FL

Classification E according to DIN EN 13501-1

General building approval Z-19.11-2021

Product Description

ROKU® Strip FL is a flexible, intumescent material that foams up without foaming pressure with thermal influence. The material is easily pliable and can be used without additional fastening material.



Application Areas

- ROKU® System SML FL and ROKU® System LAR flexibele
- As pipe closing system
- Joints, gaps or other openings
- Safety and control cabinets

Technical Data

Composition:	Foaming one-component construction material
Material structure:	Flexible, easily pliable material
Raw density [kg/m ³]:	1480 (± 10 %)
Start of reaction [°C]:	From ca. 250
Foaming rate [x-times]:	1,3 to 3-times (650 °C; 30 min; without load)
Direction of action:	Flat
Forming inflatable body:	Solid, stable material
Colour:	Orange

Supplied Forms

Standard dimension:	460 mm x 240 mm
Thicknesses:	3,3 mm to 4,4 mm

Please observe our information for processing and the safety data sheet!

*Do not expose to outdoor weather conditions or high and long-term air humidity!
If you want to use this product outdoors please contact our application technology service.*

Note

The information in this brochure is based on our knowledge and experience to date. This information does not release the user from carrying out independent tests and trials due to the various influences when processing and applying our product. It is not possible to derive a guarantee of certain properties or suitability of the product in a concrete application case based on our information. All the descriptions, drawings, photographs, data, conditions, weights etc. included may change without previous announcement; they do not constitute the contractually agreed property of the product. The recipient of our product is responsible to observe any trade mark rights and existing laws and regulations. Adhesive bonds are to be applied according to DIN 2304.